

Noise Exposure Contours for Gatwick Airport 2022 ERCD REPORT 2302



Published by the Civil Aviation Authority, 2023

Aviation House, Beehive Ring Road, Crawley, West Sussex, RH6 0YR

You can copy and use this text but please ensure you always use the most up to date version and use it in context so as not to be misleading, and credit the CAA.

Population data used in this report are based on 2011 Census data (updated for 2022) supplied by CACI Limited. © CACI Ltd 2022 All Rights Reserved.

Noise sensitive building data are from PointX © Database Right/Copyright, 118 Data Resources © Database Right/Copyright, The Local Data Company © Database Right/Copyright, VocalLink Limited © Database Right/Copyright and Ordnance Survey © Copyright and/or Database Right. All rights reserved. Licence number 10034829

Enquiries regarding the content of this publication should be addressed to: Environmental Research and Consultancy Department, Civil Aviation Authority, 5th Floor, 11 Westferry Circus, London E14 4HE

Contents

Contents	3
Summary	5
Chapter 1	7
Introduction	7
Background	7
Gatwick Airport	8
Chapter 2	9
Noise modelling methodology	9
ANCON model	9
Radar data	9
Flight tracks	9
Flight profiles	10
Noise emissions	11
Daytime traffic distributions by Noise Class	13
Night-time traffic distributions by Noise Class	14
Daytime traffic distributions by ANCON type	15
Night-time traffic distributions by ANCON type	15
Daytime traffic distributions by NPR/SID route	16
Night-time traffic distributions by NPR/SID route	16
Runway modal splits	16
Topography	17
Population and 'Points of Interest' databases	18
Chapter 3	19
Results	19
2022 summer day actual LAeq,16h contours	19
2022 summer night actual LAeq,8h contours	20
2022 summer day standard LAeq,16h contours	22
2022 summer night 10-year average modal split LAeq,8h contours	23

2022 summer day actual $L_{Aeq,16h}$ contours – comparison with 2021	25
2022 summer night actual LAeq,8h contours – comparison with 2021	26
2022 summer day standard $L_{Aeq, 16h}$ contours – comparison with 2021	27
Daytime LAeq,16h noise contour historical trend	28
Supplementary noise metric – N65 day contours	31
Supplementary noise metric – N60 night contours	33
Chapter 4	36
Conclusions	36
References	38
Figures	39
Tables	64
ANCON type descriptions	70
Glossary	74

Summary

- 1. This report presents the 2022 average summer day and night noise exposure contours generated for London Gatwick Airport. The contours in 2022 reflected the ongoing recovery of international air travel from the response to the COVID-19 pandemic.
- 2. The noise modelling used radar and noise data from Gatwick's Noise and Track Keeping (NTK) system. Mean flight tracks and lateral dispersions for each route, and average flight profiles of aircraft height, speed and thrust for each aircraft type, were calculated using these data. These model updates are undertaken every year to ensure the contours are fully representative of current operations.
- 3. Aircraft movements in the 2022 summer period recovered to nearly 90% of prepandemic levels. Average daily movements for the 16-hour daytime period in 2022 were 665.3, 266%¹ higher than the previous year (2021: 181.5). There were on average 106.0 movements per 8-hour night, an increase of 446% from 2021 (19.4).
- 4. The major recovery in 2022 summer movements caused corresponding increases in contour areas and population counts. The area of the 2022 summer day actual modal split (63% W / 37% E) 54 dB L_{Aeq,16h} contour increased by 158% to 47.3 km² (2021: 18.3 km²). The population count within this contour increased by 330% to 4,300 (2021: 1,000). The 51 dB L_{Aeq,16h} contour was plotted for the first time in 2022, and this contour enclosed an area of 88.0 km², with a population count of 12,600.
- 5. Similarly, the area of the 2022 summer day standard modal split (74% W / 26% E) 54 dB L_{Aeq,16h} contour increased by 158% to 47.3 km² (2021: 18.3 km²). The population count within this contour of 4,700 was 327% higher than the previous year (2021: 1,100).
- 6. The increase in 54 dB L_{Aeq,16h} standard modal split area of 29.0 km² can be broken down approximately as follows:
 - +37.1 km² due to changes in movement numbers and fleet mix.
 - -8.1 km² due to flight profile and noise updates based on the 2022 measurements.
- The area of the 2022 summer night actual modal split (59% W / 41% E) 48 dB
 LAeq,8h contour was 53.8 km², an increase of 279% from the previous year (2021:

¹ The percentage traffic changes given in this report are based on unrounded movement numbers.

14.2 km²). The contour enclosed a population of 6,600, which was 843% higher than in 2021 (700). The 45 dB $L_{Aeq,8h}$ contour was plotted for the first time in 2022, and this contour enclosed an area of 105.8 km², with a population count of 13,400.

- The 2022 summer night 48 dB L_{Aeq,8h} contour area assuming the 10-year average runway modal split (70% W / 30% E) was 55.1 km² (2021: 14.2 km²), enclosing a population of 7,200 (2021: 700).
- The area of the 2022 average summer day actual modal split (63% W / 37% E) N65 20-event contour was 116.6 km² (2021: 78.5 km²) and the contour enclosed a population of 17,800 (2021: 9,100).
- The area of the 2022 average summer night actual modal split (59% W / 41% E) N60 10-event contour was 163.8 km² (2021: 7.7 km²) and the contour enclosed a population of 24,100 (2021: 100).

Chapter 1 Introduction

Background

- 1.1 Each year the Environmental Research and Consultancy Department (ERCD) of the Civil Aviation Authority (CAA) calculates the noise exposure around London Gatwick Airport. Up until 2015, this work was carried out on behalf of the Department for Transport (DfT). Since the 2016 study, ERCD has been commissioned directly by Gatwick Airport Ltd (GAL).
- 1.2 The UK civil aircraft noise model ANCON, validated with noise measurements, is used to estimate the noise exposure. The model calculates the emission and propagation of noise from arriving and departing air traffic.
- 1.3 The noise exposure metric used is the Equivalent Continuous Sound Level (L_{Aeq}), and in particular L_{Aeq,16h} (07:00-23:00 local time), which is calculated over the 92-day summer period from 16 June to 15 September. The background to the use of this index is explained in DORA Report 9023 (**Ref 1**).
- 1.4 Noise exposure is depicted in the form of noise contours, i.e. lines joining places of constant L_{Aeq}, akin to the height contours shown on geographical maps or isobars on a weather chart. Historically in the UK, L_{Aeq,16h} noise contours have been plotted at levels from 57 to 72 dB, in 3 dB steps. However, the Survey of Noise Attitudes, SoNA 2014 (**Ref 2**) found that the degree of annoyance (based on the percentage of respondents highly annoyed) previously occurring at 57 dB, occurs at 54 dB. The L_{Aeq,16h} contours have therefore been plotted down to the lower level of 54 dB since 2016. At the airport's request, the 2022 L_{Aeq,16h} contours have also been plotted at 51 dB, this being defined in Government's Airspace and Noise Policy (**Ref 3**) as the daytime Lowest Observed Adverse Effect Level (LOAEL).
- 1.5 Following the publication of the Aviation Policy Framework in March 2013 (Ref 4), night-time (23:00-07:00 local time) LAeq,8h noise contours have been produced on an annual basis for the designated² airports. Night-time LAeq,8h contours have been calculated for Gatwick from 48 to 72 dB at 3 dB intervals in accordance with standard practice. Average summer night LAeq,8h contours for Gatwick were first calculated for 2013. At the airport's request, the 2022 LAeq,8h

² Heathrow, Gatwick and Stansted airports have been designated for the purpose of avoiding, limiting or mitigating the effect of noise from aircraft since 1971. The Secretary of State's powers to designate airports in England and Wales, and to set noise controls, are contained within Section 78 of the Civil Aviation Act 1982. These powers are devolved in Scotland and Northern Ireland.

contours have also been plotted at the 45 dB level, this being defined in Government's Airspace and Noise Policy (**Ref 3**) as the night-time LOAEL.

- 1.6 Day and night contours using the supplementary noise metrics N65 16-hour and N60 8-hour respectively have also been produced. N65 and N60 contours indicate the number of aircraft noise events exceeding a maximum sound level (L_{Amax}) of 65 and 60 dB respectively at a given location.
- 1.7 The objectives of this report are to explain the noise modelling methodology used to produce the 2022 contours for Gatwick Airport, to present the calculated noise contours and to assess the changes from the previous year (**Ref 5**). Long-term trends are also examined.

Gatwick Airport

- 1.8 Gatwick Airport is located approximately 28 miles (45 km) south of London and about 2 miles (3 km) north of Crawley. Aside from the nearby towns of Crawley and Horley it is situated in mostly lightly populated countryside (Figure B1 of Appendix B).
- 1.9 Gatwick Airport has one main runway, designated 08R/26L, which is 3,316 m long. The Runway 26L landing threshold is displaced by 424 m, and the Runway 08R landing threshold displaced by 393 m.³ There is also one standby runway (08L/26R) that is used when the main runway is out of operation, for example, due to maintenance work⁴. There are two passenger terminals. The layout of the runways, taxiways and passenger terminals is shown in **Figure B2**.⁵
- 1.10 In the 2022 calendar year there were approximately 218,000 aircraft movements at Gatwick (2021: 56,000) and the airport handled 32.8 million passengers (2021: 6.3 million).⁶

³ The runway threshold marks the beginning of the runway available for landing aircraft. A *displaced* threshold is a runway threshold that is not located at the physical end of the runway. A displaced threshold is often employed to give arriving aircraft sufficient clearance over an obstacle.

⁴ The main runway was resurfaced in 2022.

⁵ UK AIP, AD 2.EGKK-2-1

⁶ Source: Civil Aviation Authority (https://www.caa.co.uk/airportstatistics)

Chapter 2 Noise modelling methodology

ANCON model

- 2.1 Noise contours were calculated with the UK civil aircraft noise model ANCON (version 2.4), which is developed and maintained by ERCD on behalf of the DfT. A technical description of ANCON is provided in R&D Report 9842 (**Ref 6**). The ANCON model is also used to produce annual contours for Heathrow and Stansted airports, and a number of other UK airports.
- 2.2 ANCON is fully compliant with the latest European guidance on noise modelling, ECAC.CEAC Doc 29 (Fourth edition), published in December 2016 (**Ref 7**). This guidance document represents internationally agreed best practice as implemented in modern aircraft noise models. The Fourth edition introduced some minor changes to the modelling of start-of-roll noise, which were incorporated in the 2017 software update to ANCON (version 2.4).
- 2.3 The Gatwick modelling inputs are updated every year. The radar and noise monitoring data for the specific reporting period form the basis of the mean flight tracks, flight profiles and noise database.

Radar data

- 2.4 The noise modelling carried out by ERCD made extensive use of radar data extracted from Gatwick Airport's Noise and Track Keeping (NTK) system. The current ANOMS NTK system was installed in April 2019, replacing the previous Casper Noise NTK system. A study of the flight path information from the new ANOMS system confirmed that it continues to provide reliable flight data for the types of studies carried out by ERCD (**Ref 8**).
- 2.5 Most large airports have NTK systems, which take data from Air Traffic Control (ATC) radars and combine them with flight information such as call sign, aircraft registration, aircraft type and destination. Analyses of departure and arrival flight tracks and profiles were based on summer 2022 radar data.

Flight tracks

2.6 Aircraft departing Gatwick are required to follow specific flight paths called Noise Preferential Routes (NPRs) unless directed otherwise by ATC. NPRs were designed to avoid the overflight of built-up areas where possible. They establish a path from the take-off runway to the main UK air traffic routes and form the first part of the Standard Instrument Departure (SID) routes. The Gatwick NPR/SID routes are illustrated in **Figure B3**.

- 2.7 Associated with each NPR is a lateral swathe, which is defined by a pair of lines that diverge at 10 degrees from a point 2,000 m from start-of-roll, leading to a corridor extending 1.5 km either side of the nominal NPR centreline. Within this swathe the aircraft are considered to be flying on-track. The swathe takes account of various factors that affect track-keeping, including tolerances in navigational equipment, type and weight of aircraft, and weather conditions particularly winds that may cause drifting when aircraft are turning. Aircraft reaching an altitude of 3,000 or 4,000 ft (depending on the route) at any point along an NPR may be turned off the route by ATC onto more direct headings to their destinations a practice known as 'vectoring'. ATC may also vector aircraft from NPRs below this altitude for safety reasons, to avoid storms for example.
- 2.8 Mean flight tracks were modelled with in-house software using 24-hour radar data extracted from the Gatwick NTK system over the 92-day summer period, 16 June to 15 September. Mean departure flight tracks and associated lateral dispersions for each NPR/SID, and arrival tracks for Runways 08R and 26L using evenly spaced 'spurs' about the extended runway centrelines, were calculated. Since 2021, separate sets of mean tracks have been produced for the day and night periods.
- 2.9 Over the 2022 summer night period, the standby runway (08L/26R) was used by over 40% of movements due to resurfacing works on the main runway. Less than 2% of movements used the standby runway during the 2022 summer day period. Operations on the standby runway were modelled for both the day and night contours.
- 2.10 **Figure B4** shows a 24-hour sample of radar flight tracks from 4 September 2022.
- 2.11 Based on a visual inspection of the radar flight tracks for summer 2022, the majority of arriving aircraft during the daytime period joined the runway centrelines at distances between 14 and 26 km (7.6 and 14.0 nm) from threshold for Runway 26L, and between 13 and 25 km (7.0 and 13.5 nm) from threshold for Runway 08R. In the night-time period, most arrivals joined between 14 and 29 km (7.6 and 15.7 nm) for Runway 26L and between 15 and 27 km (8.1 and 14.6 nm) for Runway 08R.

Flight profiles

2.12 For each ANCON type, average flight profiles of height, speed and thrust versus track distance (for departures and arrivals separately) were reviewed and updated where necessary, using 2022 summer radar data. The engine power

settings required for the aircraft to follow the average height and speed profiles were calculated from data describing aircraft performance characteristics within each of the different aircraft type categories.

2.13 The application of reverse thrust following touchdown was modelled for all ANCON types where applicable. Reverse thrust was included in both the day and night contours.

Noise emissions

- 2.14 At Gatwick, the NTK system captures data from both fixed and mobile noise monitors around the airport. Noise event data for individual aircraft operations were matched to operational data provided by the airport. The Gatwick NTK system employs 5 fixed monitors positioned approximately 6.5 km from start-of-roll, together with an array of mobile monitors that can be deployed anywhere within the NTK radar coverage area.⁷
- 2.15 The noise data collected were screened by ERCD with reference to several criteria so that only reliable data were used in the analysis.
 - Noise data that lay outside a 'weather window' were discarded. This ensured that the data used were not affected by adverse meteorological conditions such as precipitation and strong winds⁸.
 - The maximum noise level of the aircraft event had to exceed the noise monitor threshold by at least 10 dB to avoid underestimates of the Sound Exposure Level (SEL).
 - Only measurements obtained from aircraft operations that passed through a 60-degree inverted cone, centred at the noise monitor, were retained in order to minimise the effects of lateral attenuation and lateral directivity.⁹
 - At a given noise monitor location, flight operations with valid noise measurements had to account for at least 75% of total overflights. This ensured that the resulting average noise level was not biased higher than the true average noise level due to missing measurements for quieter flights.
- 2.16 The ANCON model calculates aircraft noise using a noise database expressing SEL as a function of engine power setting and slant distance to the receiver also known as the 'Noise-Power-Distance' (NPD) relationship. The ANCON

⁷ Further information on the noise monitors can be found in CAP 1149 (**Ref 9**).

⁸ Wind speeds above 10 m/s, in accordance with ISO 20906 (**Ref 10**).

⁹ *Lateral attenuation* is the excess sound attenuation caused by the ground surface, which can be significant at low angles of elevation. *Lateral directivity* is the non-uniform directionality of sound radiated laterally about the roll axis of the aircraft – this is influenced to a large extent by the positioning of the engines.

noise database is continually reviewed and updated with adjustments made annually when measurements show this to be necessary.

- 2.17 For 2022, noise monitoring data from the 'Reduced Night Noise' trial were available at distances further out from the airport (beyond about 20 km), where measurements had been relatively scarce in previous years. These data were used to inform the updates to the noise model input data.
- 2.18 The most significant SEL noise database updates following noise measurements undertaken in 2022 were as follows:
 - B738 on departure, around 0.5 to 1 dB quieter at most distances. On arrival, around 0.5 dB quieter up to 20 km from threshold.
 - **EA319C** on arrival, up to 1 dB quieter beyond 10 km from threshold.
 - **EA320C** on arrival, up to 1 dB quieter beyond 6 km from threshold.
 - EA320V on departure, around 0.5 to 1 dB noisier at distances greater than 10 km from start-of-roll. On arrival, up to 2 dB quieter between 9 and 15 km from threshold, and 0.5 dB noisier beyond 18 km from threshold.
 - EA321NEO on departure, around 0.5 to 2 dB noisier. On arrival, up to about 1.5 dB noisier between 7 and 16 km from threshold.
- 2.19 Validation of L_{Amax} levels, which are the basis of the N65 and N60 contours (but not the L_{Aeq} contours), was also carried out. The most significant L_{Amax} noise database updates following noise measurements undertaken in 2022 were as follows:
 - B738 on departure, around 0.5 to 1.5 dB quieter. On arrival, 0.5 dB quieter between 11 and 20 km from threshold.
 - **EA319C** on arrival, up to 1 dB quieter beyond 10 km from threshold.
 - **EA320C** on arrival, up to 1 dB quieter beyond 6 km from threshold.
 - **EA320V** on departure, around 0.5 to 2 dB noisier beyond 12 km from startof-roll. On arrival, up to 1 dB quieter beyond 6 km from threshold.
 - EA321NEO on departure, around 1 to 2.5 dB noisier. On arrival, up to about 1 dB noisier between 5 and 11 km from threshold, and 1 dB quieter beyond 16 km from threshold.

Daytime traffic distributions by Noise Class

- 2.20 The L_{Aeq} contours were based on the daily average movements that took place during the 16-hour day (07:00-23:00 local time) and 8-hour night (23:00-07:00 local time), over the 92-day summer period from 16 June to 15 September inclusive. The source of this information was the Gatwick NTK system, which stores radar data supplemented by daily flight plans. Traffic statistics from NTK data were cross-checked with runway logs supplied by Air Navigation Solutions Ltd¹⁰ and close agreement was found.
- 2.21 Movements at Gatwick rose substantially in 2022 as international air travel continued to recover from the effects of the COVID-19 pandemic. The average number of daily movements at Gatwick over the 2022 summer day period was 665.3, 266% higher than the previous year (2021: 181.5) and almost 90% of prepandemic levels.
- 2.22 **Table C1** of **Appendix C** lists the average summer day movements by aircraft 'Noise Classes' (A to E), which are ranked in ascending order of noise emission, i.e. from least to most noisy. Starting from 2019, Noise Class C, D and E have been subdivided into 3rd and 4th generation subclasses (denoted 'C3' and 'C4' etc), with the 4th generation subclass covering the more modern, quieter aircraft as follows:
 - Noise Class C4 = B738MAX, B739MAX, EA223, EA320NEO, EA321NEO
 - Noise Class D4 = B789, B7810, EA33NEO, EA359, EA3510
 - Noise Class E4 = EA38GP, EA38R
- 2.23 In 2022, 93% of movements were within Noise Class C3/C4 (i.e. narrow-body ICAO Chapter 3/4 jet aircraft¹¹), which was 2% less than in 2021. The proportion of Noise Class C3 movements rose from 70% in 2021 to 75% in 2022. Noise Class C4 accounted for 18% of total movements, a fall of 7% from 2021.
- 2.24 Wide-body twin-engine aircraft (Noise Class D3/D4) represented 5% of total movements in 2022, the same as 2021. Noise Class D4 comprised 2% of total movements.

¹⁰ Air Navigation Solutions Ltd, a wholly owned subsidiary of the DFS Group, was the provider of air traffic control services to Gatwick Airport until October 2022, when NATS was reappointed after a break of 6 years.

¹¹ Aircraft certification noise levels are classified by the ICAO *Standards and Recommended Practices* – *Aircraft Noise: Annex 16 to the Convention on International Civil Aviation* into 'Chapter 3', 'Chapter 4' and 'Chapter 14' types. The Chapter 4 standard (applicable from 2006) is more stringent than the Chapter 3 standard (1977) and typically characterised by modern, quieter, high-bypass turbofan aircraft. The latest Chapter 14 standard is applicable to new large aircraft types presented for certification from 31 December 2017 and it represents a further level of stringency compared to the Chapter 4 standard.

- 2.25 Wide-body 4-engine aircraft (Noise Class E3/E4) made up 1% of total movements in 2022, previously having been negligible in 2021.
- 2.26 Movements by small and large propeller aircraft (Noise Classes A and B) represented less than 0.1%, and 1%, of the total respectively.
- 2.27 There were no movements in Noise Classes F, G and H, which represent the oldest and noisiest aircraft types that no longer operate at Gatwick.
- 2.28 It is estimated that almost 100%¹² of aircraft movements in the 2022 summer day period were compliant with the ICAO Chapter 4 noise standard. In addition, it is estimated that around 69% of the aircraft movements during the 2022 summer day met the latest ICAO Chapter 14 noise standard.
- 2.29 **Figure B5** illustrates the changing distribution of traffic among the 8 Noise Classes over the summer day period from 1988 to 2022 inclusive. The shift over the years to increasingly higher proportions of narrow-body jet aircraft (i.e. Noise Class C) can be clearly seen.

Night-time traffic distributions by Noise Class

- 2.30 The average number of movements over the 2022 summer night period was 106.0, a 446% increase from the previous year (2021: 19.4). Night departures increased by 254%, and night arrivals, which accounted for 69% of total summer night movements in 2022, increased by 622%.
- 2.31 **Table C2** lists the average summer night movements by aircraft Noise Class, ranked in ascending order of noise emission. Additional subclasses were introduced from 2019 for Noise Class C, D and E (see section 2.21).
- 2.32 Narrow-body jet aircraft (Noise Classes C3/C4) were responsible for 96% of movements at night in 2022, 1% less than in 2021. Noise Class C4 accounted for 28% of total night movements (2021: 41%).
- 2.33 Wide-body twin-engine aircraft (Noise Classes D3/D4) accounted for 4% of movements, 1% more than in 2021. Noise Class D4 made up 3% of total movements.
- 2.34 Wide-body 4-engine aircraft movements (Noise Classes E3/E4) at night comprised 0.1% of the total (2021: 0%).
- 2.35 There were insignificant small propeller aircraft movements (Noise Class A) and no movements within Noise Classes B, F, G and H.

¹² The percentage figure is an estimate because in some cases, detailed aircraft information (e.g. aircraft weight, engine modifications) was not readily available, so some assumptions had to be made.

2.36 It is estimated that around 99% of aircraft in the 2022 summer night period were compliant with the ICAO Chapter 4 noise standard. It is also estimated that approximately 79% of the aircraft movements at night met the ICAO Chapter 14 noise standard.

Daytime traffic distributions by ANCON type

- 2.37 A breakdown of the 2022 average summer day movements by ANCON type is provided in **Table C3**. The largest daily increases in movements were for the ANCON types EA320C (+119.4), EA319C (+109.2) and EA320V (+79.0) (note: descriptions of all the ANCON types can be found in **Table D1** of **Appendix D**). A small number of ANCON types had movement reductions that were insignificant.
- 2.38 The Airbus A320¹³ and A320neo¹⁴ aircraft families together accounted for 77% of total daytime movements in 2022.
- 2.39 **Figure B6** illustrates the movements by ANCON type for the 2022 average summer day. The most frequent ANCON types were the EA320C (171.8 movements), EA319C (147.6) and EA320V (82.6).
- 2.40 The noise dominant ANCON types on departure were, in descending order, the EA320C, EA319C and B738. For arrivals, the noise dominant ANCON types were also the EA320C, EA319C and B738. They were responsible for the highest contributions of 'noise energy', which is a function of both aircraft noise level and movement numbers.

Night-time traffic distributions by ANCON type

- A breakdown of the 2022 average summer night movements by ANCON type is provided in Table C4. The largest night-time movement increases were for the EA320C (+21.4), EA319C (+17.8), EA320V (+17.5) and EA321NEO (+12.8). There were no ANCON types that had significant movement decreases.
- 2.42 **Figure B7** illustrates the numbers of movements by ANCON aircraft type for the 2022 average summer night. The most frequent types were the EA320C (27.2), EA319C (20.5), EA320V (17.7) and EA321NEO (15.7).
- 2.43 The noise dominant ANCON types on departure were the EA320C, EA319C and EA320V. For arrivals, the noise dominant types were the EA320C, EA319C and

¹³ A319/A320/A321 (there were no A318 movements in the 2022 summer day)

¹⁴ A320neo/A321neo (there were no A319neo movements in the 2022 summer day)

EA321NEO. They were responsible for the highest contributions of 'noise energy', which is a function of both aircraft noise level and movement numbers.

Daytime traffic distributions by NPR/SID route

- 2.44 **Figure B8** shows the percentage distribution of aircraft departures by NPR/SID route for the 2022 average summer day period, with distribution figures from 2021 for comparison. Route loadings were influenced by the shift to a more typical runway modal split in 2022 (2021 was a highly atypical year with an unusually high proportion of easterly operations).
- 2.45 The 'wrap-around' route 26LAM (Route 4) had the highest loading of departure traffic in 2022 (26%), an increase of 7% from the previous year. The other most heavily-loaded routes were 26BOG (Route 7) and 26SAM (Route 1), with 19% and 18% of total departures respectively. Most easterly routes saw reductions in loading of up to 5%.

Night-time traffic distributions by NPR/SID route

- 2.46 **Figure B9** shows the percentage distribution of aircraft departures by NPR/SID route for the 2022 average summer night period, with distribution figures from 2021 for comparison. As for daytime, route loadings were influenced by the shift to a more typical runway modal split in 2022.
- 2.47 The 'wrap-around' route 26LAM (Route 4) had the highest loading of departure traffic in 2022 (28%), an increase of 8% from the previous year. The other most heavily-loaded routes were 26BOG (Route 7) and 26SAM (Route 1), with 17% and 11% of total departures respectively.
- 2.48 The highest loadings on the easterly routes were for 08CLN (Route 5) and 08SFD (Route 2), with 16% and 14% respectively. These loadings were both 5% lower than in 2021.

Runway modal splits

- 2.49 In general, aircraft will take-off and land into a headwind to maximise lift during take-off and landing. The wind direction, which varies over the course of a year, will therefore have an important influence on the usage of runways. The ratio of westerly (i.e. Runway 26L) and easterly (i.e. Runway 08R) operations is referred to as the runway modal split.
- 2.50 Two sets of contours have been produced for the 2022 summer day:
 - (a) Using the 'actual' modal split over the LAeq,16h day period; and

(b) Assuming the 'standard' modal split over the L_{Aeq,16h} day period, i.e. the long-term modal split calculated from the 20-year rolling average. For 2022, this is the 20-year period from 2003 to 2022. Use of the standard modal split enables year-on-year comparisons without the runway usage significantly affecting the contour shape.

2.51 The actual and standard daytime west / east (W / E) percentage modal splits for 2022 and 2021 are summarised in **Table 1**.

Year	Actual (W / E percentage)	Standard (W / E percentage)
2022	63 / 37	74 / 26
2021	52 / 48	74 / 26

Table 1 Gatwick summer day runway modal splits

- 2.52 The daytime actual modal split in 2022 (63% west / 37% east) had a 11% higher proportion of westerly operations compared to 2021, when there was an unusually high proportion of easterly operations. The 2022 standard modal split of 74% west / 26% east was the same as in 2021. Historical runway modal splits at Gatwick for the past 20 years are summarised in **Figure B10**.
- 2.53 The actual and 10-year average night-time modal splits for 2022 and 2021 are summarised in **Table 2**. The night-time actual runway modal split for the 2022 summer period was 59% west / 41% east. The percentage of westerly operations was 9% higher compared to 2021. The summer night 10-year (2013-2022) average modal split was 70% west / 30% east.

Year	Actual (W / E percentage)	10-year average (W / E percentage)
2022	59 / 41	70 / 30
2021	50 / 50	73 / 27

Table 2 Gatwick summer night runway modal splits

Topography

2.54 The topography around Gatwick Airport was modelled by accounting for terrain height. This was achieved by geometrical corrections for source-receiver distance and elevation angles. Other, more complex effects, such as lateral attenuation from uneven ground surfaces and noise screening/reflection effects due to topographical features, were not taken into account.

2.55 ERCD holds OS terrain height data on a 50-metre grid for the whole of Great Britain. Interpolation was performed to generate height data at each of the calculation points on the receiver grid used by the ANCON noise model. The terrain heights in the vicinity of Gatwick Airport are shown in **Figure B11**.

Population and 'Points of Interest' databases

- 2.56 Estimates were made of the numbers of people and households enclosed within the noise contours. The population data used in this report for the summer contours are a 2022 update of the 2011 Census supplied by CACI Limited.
- 2.57 The CACI population database contains data referenced at postcode level. Population and household numbers for each postcode are assigned to a single coordinate located at the postcode's centroid. The postcode data points and associated population counts for the area around Gatwick Airport are illustrated in **Figure B12**.
- 2.58 Within the extent of the 2022 average summer day standard 54 dB L_{Aeq,16h} contour, the population count using the 2022 population database was within 0.1% of the count using the 2021 database. This provides an indication of the effects of population changes in the vicinity of the airport on the results presented in Chapter 3.
- 2.59 Estimates have also been made of the numbers of noise sensitive buildings situated within the contours, using the PointX 'Points of Interest' (2022) database. For this study, the noise sensitive buildings that have been considered are community buildings, hospitals, schools (including nurseries) and places of worship.

Chapter 3 Results

2022 summer day actual LAeq,16h contours

- 3.1 The Gatwick 2022 summer day L_{Aeq,16h} noise contours generated with the actual runway modal split (63% W / 37% E) are shown in **Figure B13**. The contours are plotted from 51 to 72 dB at 3 dB intervals.
- 3.2 Cumulative estimates of the areas, populations and households within the 2022 summer day actual contours are provided in **Table 3**.

L _{Aeq,16h} (dB)	Area (km ²)	Population	Households
> 51	88.0	12,600	5,000
> 54	47.3	4,300	1,900
> 57	27.1	1,700	700
> 60	15.3	800	400
> 63	8.1	300	100
> 66	4.1	100	< 100
> 69	2.1	0	0
> 72	1.3	0	0

Table 3 Gatwick 2022 sun	nmer day actual L _{Aeq,16h} cc	ontours – area,	population	and household
estimates				
				(

Note: Populations and households are given to the nearest 100.

- 3.3 The 2022 summer day actual 51 dB L_{Aeq,16h} contour enclosed an area of 88.0 km² and a population of 12,600.
- 3.4 Estimates of the cumulative numbers of noise sensitive buildings within the 2022 summer day actual L_{Aeq,16h} contours are provided in **Table 4**.

L _{Aeq,16h} (dB)	Community buildings	Hospitals	Schools	Places of worship
> 51	6	0	19	14
> 54	1	0	6	5
> 57	1	0	4	3
> 60	0	0	1	3
> 63	0	0	1	2
> 66	0	0	0	1
> 69	0	0	0	0
> 72	0	0	0	0

Table 4 Gatwick 2022 summer day actual L_{Aeq.16h} contours – noise sensitive building estimates

2022 summer night actual LAeq,8h contours

- 3.5 The Gatwick 2022 summer night L_{Aeq,8h} noise contours generated with the actual runway modal split (59% W / 41% E) are shown in **Figure B14**. The contours are plotted from 45 to 63 dB at 3 dB intervals (note: the 66, 69 and 72 dB contours have been omitted for clarity).
- 3.6 Cumulative estimates of the areas, populations and households within the 2022 summer night actual L_{Aeq,8h} contours are provided in **Table 5**.
- 3.7 The 2022 summer night actual 45 dB L_{Aeq,8h} contour enclosed an area of 105.8 km² and a population of 13,400.
- 3.8 Estimates of the cumulative numbers of noise sensitive buildings within the 2022 summer night actual L_{Aeq,8h} contours are provided in **Table 6**.

L _{Aeq,8h} (dB)	Area (km²)	Population	Households
> 45	105.8	13,400	5,300
> 48	53.8	6,600	2,600
> 51	29.2	1,600	700
> 54	16.2	700	300
> 57	8.9	300	100
> 60	4.7	100	< 100
> 63	2.3	0	0
> 66	1.4	0	0
> 69	0.9	0	0
> 72	0.5	0	0

Table 5 Gatwick 2022 summer night actual $L_{Aeq,8h}$ contours – area, population and household estimates

Note: Populations and households are given to the nearest 100.

L _{Aeq,8h} (dB)	Community buildings	Hospitals	Schools	Places of worship
> 45	6	1	16	13
> 48	3	0	13	7
> 51	1	0	3	3
> 54	0	0	1	3
> 57	0	0	0	2
> 60	0	0	0	1
> 63	0	0	0	0
> 66	0	0	0	0
> 69	0	0	0	0
> 72	0	0	0	0

Table 6 Gatwick 2022 summer night actual LAeg,8h contours – noise sensitive building estimates

2022 summer day standard LAeq,16h contours

- 3.9 The Gatwick 2022 summer day L_{Aeq,16h} noise contours generated with the standard runway modal split (74% W / 26% E) are shown in **Figure B15**. The contours are plotted from 51 to 72 dB at 3 dB intervals.
- 3.10 Cumulative estimates of the areas, populations and households within the 2022 summer day standard L_{Aeq,16h} contours are provided in **Table 7**.

estimates			
L _{Aeq,16h} (dB)	Area (km²)	Population	Households
> 51	89.6	12,500	5,000
> 54	47.3	4,700	2,000
> 57	27.0	1,600	700
> 60	15.3	600	200
> 63	8.1	300	100
> 66	4.1	100	< 100
> 69	2.1	0	0

Table 7 Gatwick 2022 summer day standard LAeq,16h contours – area, population and household estimates

Note: Populations and households are given to the nearest 100.

3.11 The 2022 summer day standard 51 dB L_{Aeq,16h} contour enclosed an area of 89.6 km² and a population of 12,500.

1.3

3.12 Estimates of the cumulative numbers of noise sensitive buildings within the 2022 summer day standard L_{Aeq,16h} contours are provided in **Table 8**.

0

> 72

0

L _{Aeq,16h} (dB)	Community buildings	Hospitals	Schools	Places of worship
> 51	6	0	19	15
> 54	2	0	6	6
> 57	1	0	3	3
> 60	0	0	1	3
> 63	0	0	1	2
> 66	0	0	0	1
> 69	0	0	0	0
> 72	0	0	0	0

Table 8 Gatwick 2022 summer day standard L_{Aeg,16h} contours – noise sensitive building estimates

2022 summer night 10-year average modal split LAeq,8h contours

- 3.13 The Gatwick 2022 summer night L_{Aeq,8h} noise contours generated with the 10-year average (2013-2022) summer night period runway modal split (70% W / 30% E) are shown in Figure B16. The contours are plotted from 45 to 63 dB at 3 dB intervals (note: the 66, 69 and 72 dB contours have been omitted for clarity).
- 3.14 Cumulative estimates of the areas, populations and households within the 2022 summer night 10-year average modal split LAeq,8h contours are provided in Table 9.
- 3.15 The 2022 summer night 10-year average modal split 45 dB L_{Aeq,8h} contour enclosed an area of 103.7 km² and a population of 13,900.
- 3.16 Estimates of the cumulative numbers of noise sensitive buildings within the 2022 summer night 10-year average modal split LAeq,8h contours are provided in Table 10.

L _{Aeq,8h} (dB)	Area (km²)	Population	Households
> 45	103.7	13,900	5,500
> 48	55.1	7,200	2,800
> 51	29.4	1,900	800
> 54	16.3	800	300
> 57	8.9	300	100
> 60	4.6	100	< 100
> 63	2.3	0	0
> 66	1.4	0	0
> 69	0.9	0	0
> 72	0.5	0	0

Table 10 Gatwick 2022 summer night 10-year average modal split LAeq,8h contours – area, population and household estimates

Note: Populations and households are given to the nearest 100.

Table 10 Gatwick 202	2 summer night 10)-year average	modal split L _{Aeg,8h}	contours -	- noise sensitive
building estimates			- .		

L _{Aeq,8h} (dB)	Community buildings	Hospitals	Schools	Places of worship
> 45	6	1	18	12
> 48	2	0	14	9
> 51	1	0	2	3
> 54	1	0	1	3
> 57	0	0	0	2
> 60	0	0	0	1
> 63	0	0	0	0
> 66	0	0	0	0
> 69	0	0	0	0
> 72	0	0	0	0

2022 summer day actual L_{Aeq,16h} contours – comparison with 2021

- 3.17 The Gatwick 2022 and 2021 summer day actual modal split L_{Aeq,16h} contours are compared in **Figure B17**. Comparisons are made from the 54 dB level as the 51 dB contour was not produced for 2021. For clarity, the 2022 and 2021 contours are only plotted at the levels 54, 60 and 66 dB.
- 3.18 **Table 11** summarises the areas, populations and percentage changes from 2021 to 2022.

L _{Aeq,16h} (dB)	2021 area (km²)	2022 area (km²)	Area change	2021 population	2022 population	Population change
> 54	18.3	47.3	+158%	1,000	4,300	+330%
> 57	9.7	27.1	+179%	400	1,700	+325%
> 60	5.2	15.3	+194%	100	800	+700%
> 63	2.7	8.1	+200%	< 100	300	(n/a)
> 66	1.6	4.1	+156%	0	100	(n/a)
> 69	1.0	2.1	+110%	0	0	(n/a)
> 72	0.6	1.3	+117%	0	0	(n/a)

Table 11 Gatwick 2021 and 2022 summer day actual LAeq,16h contours – area and population estimates

Note: The 2021 and 2022 summer day actual runway modal splits were 52% W / 48% E and 63% W / 37% E respectively.

- 3.19 The 54 dB L_{Aeq,16h} contour area increased by 158% in 2022 and area increases of up to 200% were also found at the higher contour levels. This resulted predominantly from the 266% rise in movements.
- 3.20 The population count for the 54 dB contour increased by 330% in 2022 and there were also increases at the higher contour levels.
- 3.21 Percentage changes in contour area are not necessarily accompanied by similar changes in enclosed population because of the uneven distribution of populations around the airport.

2022 summer night actual L_{Aeq,8h} contours – comparison with 2021

- 3.22 The Gatwick 2022 and 2021 summer night actual modal split L_{Aeq,8h} contours are compared in **Figure B18**. Comparisons are made from the 48 dB level as the 45 dB contour was not produced for 2021. For clarity, the 2022 and 2021 contours are only plotted at the levels 48, 54 and 60 dB.
- 3.23 **Table 12** summarises the areas, populations and percentage changes from 2021 to 2022.

L _{Aeq,8h} (dB)	2021 area (km²)	2022 area (km²)	Area change	2021 population	2022 population	Population change
> 48	14.2	53.8	+279%	700	6,600	+843%
> 51	7.5	29.2	+289%	200	1,600	+700%
> 54	4.0	16.2	+305%	< 100	700	(n/a)
> 57	2.1	8.9	+324%	< 100	300	(n/a)
> 60	1.3	4.7	+262%	0	100	(n/a)
> 63	0.8	2.3	+188%	0	0	(n/a)
> 66	0.5	1.4	+180%	0	0	(n/a)
> 69	0.3	0.9	+200%	0	0	(n/a)
> 72	0.2	0.5	+150%	0	0	(n/a)

Table 12 Gatwick 2021 and 2022 summer night actual LAeq,8h contours – area and population estimates

Note: The 2021 and 2022 summer night actual runway modal splits were 50% W / 50% E and 59% W / 41% E respectively.

- 3.24 The 48 dB L_{Aeq,8h} contour area in 2022 increased by 279% compared to 2021 due to the movement increase of 446%. Area increases of up to 324% were seen at the higher contour levels.
- 3.25 The population count increased by 843% within the 48 dB L_{Aeq,8h} contour and by 700% at the 51 dB contour level.

2022 summer day standard L_{Aeq,16h} contours – comparison with 2021

- 3.26 The Gatwick 2022 and 2021 summer day standard modal split L_{Aeq,16h} contours are compared in **Figure B19**. Comparisons are made from the 54 dB level as the 51 dB contour was not produced for 2021. For clarity, the 2022 and 2021 contours are only plotted at the levels 54, 60 and 66 dB.
- 3.27 **Table 13** summarises the areas, populations and percentage changes from 2021 to 2022.
- 3.28 The standard contours normally provide a clearer indication than the actual contours of 'fleet noise level' changes from year to year, because they minimise the effects of any differences between the ratios of westerly to easterly operations.

Table 13 Gatwick 2021 and 2022 summer day standard LAeq,16h contours – area and population estimates

L _{Aeq,16h} (dB)	2021 area (km²)	2022 area (km²)	Area change	2021 population	2022 population	Population change
> 54	18.3	47.3	+158%	1,100	4,700	+327%
> 57	9.7	27.0	+178%	300	1,600	+433%
> 60	5.2	15.3	+194%	100	600	+500%
> 63	2.7	8.1	+200%	< 100	300	(n/a)
> 66	1.6	4.1	+156%	0	100	(n/a)
> 69	1.0	2.1	+110%	0	0	(n/a)
> 72	0.6	1.3	+117%	0	0	(n/a)

Note: The 2021 and 2022 summer day standard runway modal splits were both 74% W / 26% E.

- 3.29 The 2022 standard modal split 54 dB L_{Aeq,16h} contour area increased by 158% compared to 2021 and there were area increases of up to 200% at the higher contour levels.
- 3.30 The 29.0 km² increase in the 54 dB L_{Aeq,16h} area can be broken down approximately as follows:
 - +37.1 km² due to changes in movement numbers and fleet mix.
 - -8.1 km² due to flight profile and noise updates based on the 2022 measurements.
- 3.31 There was a 327% population increase in 2022 at the 54 dB contour level and even higher increases at the 57 and 60 dB contour levels.

Daytime LAeq,16h noise contour historical trend

3.32 **Figure B20** shows how the 57 dB L_{Aeq,16h} day actual modal split contour has changed in area and population terms since 1988 by comparison with the total annual (365-day) aircraft movements. Actual modal split data are used in this figure because standard modal split contours were not produced prior to 1995.

Movements

- 3.33 Aircraft movements reached a low in 1991 (the year of the First Gulf War) and did not return to 1990 levels until 1995. From 1995 to 2000 they increased steadily. From 2000 to 2002 movements decreased, possibly as a consequence of the terrorist attacks on 11 September 2001. There was little change in the total annual number of movements from 2002 to 2003, but annual movements rose steadily from 2004 to 2007. However, the annual movement figure for 2008 fell by 1% from 2007 this may be attributed to the fluctuating oil price and economic downturn. The annual movements fell even further in 2009, by 4%, as the global recession continued to impact upon the aviation industry.
- 3.34 Movements dropped for the third year in a row in 2010, by a further 5%. This was due in part to the volcanic ash crisis in April and adverse winter weather conditions. However, there was a recovery in 2011 from the adverse events of the previous year as traffic levels rose by 4%. In 2012 traffic levels fell by 2% following a reduction in charter flights at Gatwick. However, movement numbers increased from 2013 through to 2017 as demand returned. Movements then reduced by 1% in 2018, caused in part by serious disruptions in December 2018 following drone sightings at the airport. Movements rose slightly (by 0.4%) in 2019.
- 3.35 The COVID-19 global pandemic in 2020 caused a 72% fall in annual movements at Gatwick. There was a further 30% drop in annual movements in 2021 as the pandemic severely reduced flights in the first half of the year and international travel restrictions only started to ease at the start of the summer. However, in 2022 there was a major rise in annual movements as air travel recovered.

Areas

3.36 From 1988 to 1993, the area within the 57 dB L_{Aeq,16h} contour diminished and then increased until 1996. From 1996 onwards the area decreased each year but levelled off between 1999 and 2000. In 2001, the area fell by 22% relative to the previous year, and in 2002, the contour area decreased by 19% relative to 2001. From 2002 to 2008 the contour area fluctuated within a narrow range from 45 to 49 km². However, the area fell below this range to 41 km² in 2009, and dropped further in 2010 to 39.6 km², which at the time was the smallest ever area calculated for Gatwick, as the global recession impacted upon the aviation industry.

- 3.37 Since 2011 the contour area has fluctuated within the range 40-44 km². The contour area increased by 2% in 2011 to 40.4 km² as movements started to recover. In 2012 the area was again higher by 2%, this time mainly due to some changes in the fleet mix. The 2013 contour area reduced by 1% from 2012 despite a rise in movements, largely because of fleet mix changes in favour of quieter types. However, in 2014 the contour area increased by 3% as total movements rose again and some large twin-turboprop aircraft were replaced by narrow-body jets. There was a 1% area increase in 2015 as higher numbers of movements were largely offset by noise adjustments to some of the ANCON aircraft types in the light of monitoring data. In 2016 the area increased again to 44.2 km² as movements rose by 4%. However, in 2017 the area fell by 3% as noise levels reduced for the Airbus A319/A320 aircraft on arrival, which was likely the result of most of these types having received the FOPP (Fuel Over Pressure Protector) modification to reduce approach noise. In 2018 the area fell again, this time by 6%, primarily because noise measurements showed that the noise dominant aircraft types were quieter on arrival. The area decreased for the third year running in 2019 (by 3%) to its lowest ever level of 38.7 km², as the proportion of more modern, quieter types (such as the Airbus A320neo and A321neo) in the fleet mix increased.
- 3.38 The COVID-19 pandemic had unprecedented impacts on air travel in 2020, causing a 72% drop in annual movements at Gatwick and an 82% reduction in the 57 dB contour area, which fell to an all-time low of 7.0 km². In 2021, the contour area increased by 38% as movements recovered during the summer, and 2022 saw a 179% area increase following a sustained recovery in air travel.

Populations

3.39 The population numbers within the contours have generally moved in line with the areas. They dropped to the lowest ever level in 2010 when the area was also at its lowest, but since 2011 have fluctuated between approximately 3,000-4,000. The 19% rise in population for 2012 was largely the result of the contour extending over a densely populated area (Lingfield). In 2013, the population dropped by 11% as the higher proportion of easterly movements caused the contour to retreat from Lingfield. The population count increased by 2% in 2014 following the inclusion of Gatwick immigration removal centre residents in the population database for the first time. An 11% rise in population occurred in 2015 as the contour extended over Lingfield, after a shift in the runway modal split back to a more typical figure. The population increased again in 2016 as an 11% higher proportion of westerly operations extended the contour over parts of Lingfield. However, in 2017 the population decreased by 2% following an area reduction. The population also fell in 2018 (this time by 31%) as quieter aircraft on arrival and a 10% reduction in westerly movements shifted the contour away from Lingfield. The population count decreased (by 9%) for the third year running

in 2019 to its lowest ever level of 2,550 as the contour area also fell to its lowest level since 1988.

3.40 The 82% contour area reduction in 2020 meant the population within the 57 dB contour also fell to the lowest level ever recorded (150). In 2021, the 38% increase in contour area caused the population to increase by 100%. The population rose further in 2022 by 325% as the contour area expanded by 179%.

Supplementary noise metric – N65 day contours

3.41 Contours using the supplementary noise metric N65¹⁵ have been produced for the 2022 summer day period, using the same modelling input data as the L_{Aeq,16h} day actual modal split (63% W / 37% E) contours. The contours are shown in **Figure B21**, plotted at levels 20, 50, 100, 200 and 500 events, and overlaid onto the 2021 results plotted at the same levels. Estimates of area, population and households are summarised in **Table 14**.

Table 14 Gatwick 2022 summer day actual modal split N65 contours – area, population and household estimates

N65	Area (km²)	Population	Households
> 20	116.6	17,800	7,300
> 50	80.6	11,300	4,700
> 100	63.8	7,100	2,800
> 200	45.2	5,000	2,000
> 500	1.9	< 100	0

Note: Populations and households are given to the nearest 100. The 2022 summer day actual runway modal split was 63% W / 37% E.

- 3.42 The 2022 summer day actual N65 20-event contour enclosed an area of 116.6 km^2 (2021: 78.5 km²) and a population of 17,800 (2021: 9,100).
- 3.43 Estimates of the cumulative numbers of noise sensitive buildings within the 2022 summer day actual N65 contours are provided in **Table 15**.

Table 15 Gatwick 2022 summer day actual modal split N65 contours – noise sensitive building estimates

N65	Community buildings	Hospitals	Schools	Places of worship
> 20	9	0	23	15
> 50	7	0	18	11
> 100	3	0	14	8
> 200	3	0	9	7
> 500	0	0	0	1

¹⁵ N65 contours show the number of aircraft noise events exceeding 65 dB L_{Amax}.

3.44 N65 contours have also been produced for the 2022 summer day period with the standard modal split (74% W / 26% E). The contours are shown in **Figure B22**, plotted at levels 20, 50, 100, 200 and 500 events, and overlaid onto the 2021 results plotted at the same levels. Estimates of area, population and households are summarised in **Table 16**.

able 16 Gatwick 2022 summer day standard modal split N65 contours – area, population and	b
ousehold estimates	

N65	Area (km²)	Population	Households
> 20	113.0	16,700	6,900
> 50	80.3	11,000	4,600
> 100	60.1	6,100	2,400
> 200	47.2	5,300	2,100
> 500	1.9	< 100	0

Note: Populations and households are given to the nearest 100. The 2022 summer day standard runway modal split was 74% W / 26% E.

- 3.45 The 2022 summer day standard N65 20-event contour enclosed an area of 113.0 km² (2021: 78.3 km²) and a population of 16,700 (2021: 10,100).
- 3.46 Estimates of the cumulative numbers of noise sensitive buildings within the 2022 summer day standard N65 contours are provided in **Table 17**.

Table 17 Gatwick 2022 summer day standard modal split N65 contours – noise sensitive building estimates

N65	Community buildings	Hospitals	Schools	Places of worship
> 20	9	0	22	15
> 50	7	0	18	11
> 100	3	0	14	11
> 200	3	0	9	8
> 500	0	0	0	1

Supplementary noise metric – N60 night contours

- 3.47 Contours using the supplementary noise metric N60¹⁶ have been produced for the 2022 summer night period, using the same modelling input data as the L_{Aeq,8h} night actual modal split (59% W / 41% E) contours.
- Figure B23 shows the 2022 N60 contours plotted at the 10, 20, 50 and 100-event levels. Also overlaid are the 2021 results plotted at the 10-event level. Estimates of area, population and households are summarised in Table 18.

Table 18 Gatwick 2022 summer night actual modal split N60 contours – area, population and household estimates

N60	Area (km²)	Population	Households
> 10	163.8	24,100	9,500
> 20	112.9	12,400	4,900
> 50	36.2	2,600	1,100
> 100	0.6	0	0

Note: Populations and households are given to the nearest 100. The 2022 summer night actual runway modal split was 59% W / 41% E.

- 3.49 The 2022 summer night actual N60 10-event contour enclosed an area of 163.8 km² (2021: 7.7 km²) and a population of 24,100 (2021: 100).
- 3.50 Estimates of the cumulative numbers of noise sensitive buildings within the 2022 summer night actual N60 contours are provided in **Table 19**.

Table 19 Gatwick 2022 summer night actual modal split N60 contours – noise sensitive building estimates

N60	Community buildings	Hospitals	Schools	Places of worship
> 10	14	1	27	22
> 20	6	1	17	12
> 50	1	0	6	4
> 100	0	0	0	0

¹⁶ N60 contours show the number of aircraft noise events exceeding 60 dB L_{Amax}.

3.51 N60 contours have also been produced for the 2022 summer night period with the L_{Aeq,8h} night 10-year average modal split (70% W / 30% E). The contours are shown in **Figure B24**, plotted at the 10, 20, 50 and 100-event levels, and overlaid onto the 2021 results plotted at the 10-event level. Estimates of area, population and households are summarised in **Table 20**.

Table 20 Gatwick 2022 summer night 10-year average modal split N60 contours – area, population and household estimates

N60	Area (km²)	Population	Households
> 10	160.6	19,100	7,500
> 20	118.7	13,000	5,200
> 50	40.7	6,800	2,700
> 100	0.6	0	0

Note: Populations and households are given to the nearest 100. The 2022 summer night 10-year average runway modal split was 70% W / 30% E.

- 3.52 The 2022 summer night 10-year average modal split N60 10-event contour enclosed an area of 160.6 km² (2021: 7.2 km²) and a population of 19,100 (2021: 200).
- 3.53 The above changes in N60 contour area compared to 2021 can be attributed to the 446% increase in movements at night in 2022.
- 3.54 'Number Above' (N) contours can be highly sensitive to small changes in movement numbers or differences in runway modal splits. Because N-contours are based on counts of aircraft events above a specified maximum noise level threshold, step changes in area can occur if the Number Above count just goes above or below the event level of interest (e.g. 10 events) at a particular location. Changes in area enclosed by LAeq contours due to such changes, by contrast, are more gradual, due to contour area being proportional to noise energy, i.e. not subject to specific threshold requirements.
- 3.55 Estimates of the cumulative numbers of noise sensitive buildings within the 2022 summer night 10-year average modal split N60 contours are provided in Table 21.

Table 21 Gatwick 2022 summer night 10-year average modal split N60 contours – noise sensitive building estimates

N60	Community buildings	Hospitals	Schools	Places of worship
> 10	13	1	25	22
> 20	7	1	19	14
> 50	2	1	14	9
> 100	0	0	0	0

Chapter 4 Conclusions

- 4.1 Year 2022 average summer day L_{Aeq,16h} and night L_{Aeq,8h} noise exposure contours have been generated for Gatwick Airport using the ANCON noise model.
- 4.2 Movements over the 2022 summer day period rose by 266% to 665.3 from 2021 (181.5), as international air travel continued its recovery from the effects of the COVID-19 global pandemic. The 2022 summer day actual modal split (63% W / 37% E) 54 dB LAeq.16h contour area increased by 158% to 47.3 km² (2021: 18.3 km²). The population count within this contour rose by 330% in 2022 to 4,300 (2021: 1,000).
- 4.3 The 2022 summer day standard modal split (74% W / 26% E) 54 dB L_{Aeq,16h} contour area also increased by 158%, to 47.3 km² (2021: 18.3 km²). The population enclosed by this contour (4,700) was 327% higher than the previous year (2021: 1,100).
- 4.4 The 158% or 29.0 km² increase in the 54 dB L_{Aeq,16h} area can be broken down approximately as follows:
 - +37.1 km² due to changes in movement numbers and fleet mix.
 - -8.1 km² due to flight profile and noise updates based on the 2022 measurements.
- 4.5 The 2022 summer 8-hour night movements increased by 446% to 106.0 from 2021 (19.4). The 2022 summer night actual modal split (59% W / 41% E) 48 dB LAeq.8h contour area was 53.8 km², an increase of 279% from 2021 (14.2 km²). The population count within this contour was 6,600, an 843% increase from 2021 (700). The area increase can be attributed primarily to the 446% rise in movements.
- The 2022 summer night 48 dB L_{Aeq,8h} contour area assuming the 10-year average runway modal split (70% W / 30% E) was 55.1 km² (2021: 14.2 km²), enclosing a population of 7,200 (2021: 700).
- 4.7 Contours for the supplementary noise metric N65 have been produced for the 2022 average summer 16-hour day period. The area of the N65 20-event actual modal split (63% W / 37% E) contour was 116.6 km² (2021: 78.5 km²), enclosing a population of 17,800 (2021: 9,100). With the standard modal split (74% W / 26% E), the N65 20-event contour area was 113.0 km² (2021: 78.3 km²), enclosing a population of 16,700 (2021: 10,100).
4.8 Supplementary noise metric N60 contours have also been produced for the 2022 average summer 8-hour night period. The area of the N60 10-event actual modal split (59% W / 41% E) contour was 163.8 km² (2021: 7.7 km²), enclosing a population of 24,100 (2021: 100). With the 10-year average modal split (70% W / 30% E), the N60 10-event area was 160.6 km² (2021: 7.2 km²), enclosing a population of 19,100 (2021: 200).

APPENDIX A

References

- 1. Critchley J B, Ollerhead J B, *The Use of Leq as an Aircraft Noise Index*, DORA Report 9023, September 1990.
- 2. Civil Aviation Authority, *Survey of Noise Attitudes (2014): Aircraft*, CAP 1506, February 2017.
- 3. Department for Transport, *Consultation Response on UK Airspace Policy: A framework for balanced decisions on the design and use of airspace,* Cm 9520, October 2017.
- 4. Department for Transport, Aviation Policy Framework, Cm 8584, March 2013.
- 5. Civil Aviation Authority, *Noise Exposure Contours for Gatwick Airport 2021*, ERCD Report 2202, June 2022.
- Ollerhead J B, Rhodes D P, Viinikainen M S, Monkman D J, Woodley A C, *The UK Civil Aircraft Noise Contour Model ANCON: Improvements in Version 2*, R&D Report 9842, June 1999.
- 7. European Civil Aviation Conference, *Report on Standard Method of Computing Noise Contours around Civil Airports*, ECAC.CEAC Doc 29, Fourth edition, December 2016.
- 8. Civil Aviation Authority, *Flight path accuracy of the Gatwick Noise and Track Keeping System*, CAP 1878, March 2020.
- 9. Civil Aviation Authority, *Noise Monitor Positions at Heathrow, Gatwick and Stansted Airports*, CAP 1149, 8th edition, March 2022.
- 10. ISO 20906:2009 Acoustics Unattended monitoring of aircraft sound in the vicinity of airports.

APPENDIX B

Figures











Figure B5 Gatwick Noise Class trend 1988-2022

Note: The percentages from 1990 onwards relate to the average 16-hour L_{eq} day; before 1990 the percentages relate to the average 12-hour NNI day (07:00-19:00 local time). Also, the percentages before 1992 are based on departures only, from 1992 they relate to total movements.

Key to Noise Classes

Noise Class	Description
Α	Small propeller (single/twin piston and turboprop light aircraft)
В	Large propeller (twin and 4-propeller aircraft), e.g. ATR-42, BAe ATP
С	Narrow-body aircraft (up to 2018), e.g. Airbus A319, Boeing 737-800
C3	3 rd generation narrow-body aircraft (from 2019), e.g. Airbus A319, Boeing 737-800
C4	4 th generation narrow-body aircraft (from 2019), e.g. Airbus A320neo
D	Wide-body twins (up to 2018), e.g. Airbus A330, Boeing 777-200
D3	3 rd generation wide-body twins (from 2019), e.g. Airbus A330, Boeing 777-200
D4	4 th generation wide-body twins (from 2019), e.g. Airbus A350-900, Boeing 787-9
E	Wide-body 3 or 4-engine aircraft (up to 2018), e.g. Airbus A380, Boeing 747-400
E3	3 rd generation wide-body 4-engine aircraft (from 2019), e.g. Boeing 747-400
E4	4 th generation wide-body 4-engine aircraft (from 2019), e.g. Airbus A380
F	1 st generation wide-body 3 or 4-engine aircraft, e.g. Boeing 747-200
G	2 nd generation narrow-body twins (including Ch.2 and hush-kitted versions), e.g. Boeing 737-200
Н	1 st generation narrow-body 3 or 4-engine aircraft (including hush-kitted versions), e.g. Boeing 707



Figure B6 Gatwick 2022 summer day movements by ANCON type











Figure B10 Gatwick summer day runway modal splits 2003-2022





ter la te
Mood And Market And
Sharper Sh
ROMAN ROAD 10 FOR STORE
Betch State
agate of the free of the second
E Charles Constant of the second
Average Ale Ale Ale Ale Ale Ale Ale Ale Ale Al

International of the second se	additume additume Crowhunst Crowhunst Crowhunst Crowhunst Edenbridge additume Edenbridge Additume Edenbridge Additume Edenbridge Additume Edenbridge Additum	bindige Condition of the Alarman Park of the A	Saint Hill And Harmerwood	Sharpthome Coleman of Friar's Friar's Start Wyth Cross Coleman of Coleman of Friar's Start Wyth Cross Coleman of Coleman	Danehill Muthey School Hursey
lation Kingswood Holley II Chaldon Latin Kingswood Holley II Chaldon C	According to the solution of t	Marine Honord Ho	Broadfield Annual Broadfield A	A Prasto Ougate Portáge ST LEONARD S FOREST Handcross Stapleánid Stapleánid	Paeding Lower Clarking Brook Street Lower Clarking Clarki
Micommon A Hertham LEATHERHEAD M Hertham Micommon A Hertham Hertham Microsoft A Hertham Hertham Hertham A	Entry Field	HUT IVOG HUT IVOG RAT HUT IVOG Forest	Idd Chroways Greed (S4) (S4) (S4) (S4) (S4) (S4) (S4) (S4)	Tisman's A281 Common Bucks Green A29 Common Warman A29 Common Warman A29 Common Mainings Common A204 Ichingfield A10 Mannings	Nuthurist Billings hurst Billings hurst Bil

Ham Part of the second se	LEST 16105.
Cowden	ASHD ASHD ASHD ASHD ASHD ASHD ASHD ASHD
Column Hill	Ashurst Hammer Ashurst Hammer Ashurst
Search Se	Entropy of the second s
	Summyside
dge Gritter	Sharphth Sharphth Sharphth Sharphth Sharphth Sharphthe S
Felbri	2023. AI
	Architecture
odstom Sletching	Abbey We was the way of the way o
	Constant of the second se
Merstein States and States a	Skipter Skipter
	auffrield Stanuch
locith Leigh	Lambs Geo
Parkigate Chairig	
Contraction of the second	- Contraction of the second se
Station Station	
Polesten a Bolesten Coldha Jay	Line for the former of the for
Contraction of Contra	Minurst Gr gwick A20 Bliss Ba
And the second structure of the second structure second s	

River Mutery Mealin Ashtur Ste	105.
	lgate Hungt
6 Sur Stated Sur Stated Sur Stated Sur Stated Sur	mber 1
	PREST
A d d d d d d d d d d d d d d d d d d d	4S
Services Ser	servec
FFOURST FERENCE	ghts re
	3. All ri
Sharp	Menus ins
	Ardingly Ardined
MARTIN States of the second st	Iown o
CATE CATE Control Con	
	Budger
	25 k
Constant and the second s	Star Star
	Cross M
	ST Hand
alton	FORE Beeedi
	muturist
	15
Stront Strong	
Paire	Southware
	S S S S S S S S S S S S S S S S S S S
Horskie	Etve
alacter from the second s	
	A A A A A A A A A A A A A A A A A A A
	Commandation and a stress of the stress of t



ε

Ockley

yes

Austichur Holmwood

arbour

Holmwood

Station

South

noi

ja l

Crown copyright 2023. All rights reserved. Licence number 100016105.

Nestcott

Wafrinham,

Winterfold

hook

Broadbridge

eath

0





q,16h contours
) L _{Ae}
Ш%
/ 26
M %
(74°
2021
pu
Ē
26%
Ň
74%
2022 (
lard
stanc
day :
ner
Imus
ick s
3atw
19 6
re B
ngi:





Sterinan Brine B Brine	Coleman Hatch 1 2 2 00016105.
Safriess Version Contraction C	202 - 202 -
Eden Eden Born Bark	d. Licence
Octed A	Marpthome Meynes Meynes Meynes
Solsfield	ightrook definigly
ITERHAM ITERHAM Included Included Inc	West Hoa
Landon Contraction	Crown o
Solution and Sol	aplefield
	Potrage Potrage ST Handcross
on the land of high high high high high high high hig	ST LEON
Brockham Brockham	In the second se
Great Great Bookhammer Westgrout	Broadfridg
A A A A A A A A A A A A A A A A A A A	Simold Simold
East Horsey Horsey Horsey Horsey Horsey Hart State	Rudgwick Reen A281 A2
and frink to be a start to be	E AL



rley een

ere

avs

0





APPENDIX C Tables

Noise Class	Description	2022 movements	2022 percentage	2021 percentage
А	Small propeller aircraft	< 0.1	< 0.1%	0.1%
В	Large propeller aircraft	9.8	1%	0.3%
С	Narrow-body aircraft	(619.9)	(93%)	(95%)
N C3	3 rd generation narrow-body (e.g. B738)	497.8	75%	70%
\ C4	4 th generation narrow-body (e.g. EA320NEO)	122.1	18%	25%
D	Wide-body twin-engine aircraft	(32.0)	(5%)	(5%)
1 D3	3 rd generation wide-body twin-engine (e.g. B763G)	17.7	3%	3%
1 D4	4 th generation wide-body twin-engine (e.g. B789)	14.3	2%	2%
E	Wide-body 4-engine aircraft	3.6	(1%)	(< 0.1%)
N E3	3 rd generation wide-body 4-engine (e.g. B744G)	< 0.1	< 0.1%	< 0.1%
N E4	4 th generation wide-body 4-engine (e.g. EA38R)	3.6	1%	0%
	Total	665.3	100%	100%

Table C1 Gatwick 2022 average summer day movements by Noise Class

Note: Noise Classes C, D and E have each been subdivided into two separate subclasses since 2019.

Noise Class	Description	2022 movements	2022 percentage	2021 percentage
А	Small propeller aircraft	< 0.1	< 0.1%	0.2%
В	Large propeller aircraft	0.0	0%	0.1%
С	Narrow-body aircraft	(101.3)	(96%)	(97%)
A C3	3 rd generation narrow-body aircraft (e.g. B738)	71.2	67%	56%
) C4	4 th generation narrow-body aircraft (e.g. EA320NEO)	30.1	28%	41%
D	Wide-body twin-engine aircraft	(4.5)	(4%)	(3%)
1 D3	3 rd generation wide-body twin-engine aircraft (e.g. B763G)	1.4	1%	1%
1 D4	4 th generation wide-body twin-engine aircraft (e.g. B789)	3.1	3%	2%
E	Wide-body 4-engine aircraft	(0.1)	(0.1%)	(0%)
N E3	3 rd generation wide-body 4-engine aircraft (e.g. B744G)	< 0.1	< 0.1%	0%
N E4	4 th generation wide-body 4-engine aircraft (e.g. EA38R)	0.1	< 0.1%	0%
	Total	106.0	100%	100%

Table C2 Gatwick 2022 average summer night movements by Noise Class

Note: Noise Classes C, D and E have each been subdivided into two separate subclasses since 2019.

ANCON	2021	2021	2021 total	2022	2022	2022 total	Change	Change	Change
type	departures	arrivals		departures	arrivals		departures	arrivals	total
B733	0.0	0.0	0.0	0.1	0.1	0.1	+0.1	+0.1	+0.1
B738	11.4	11.1	22.5	34.9	34.3	69.2	+23.5	+23.2	+46.7
B738MAX	2.6	2.5	5.1	11.6	9.1	20.7	+8.9	+6.6	+15.5
B739MAX	0.0	0.0	0.0	1.8	1.8	3.6	+1.8	+1.8	+3.6
B753	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
B757E	0.4	0.5	0.9	0.8	0.6	1.5	+0.4	+0.2	+0.5
B763G	0.1	0.1	0.3	0.1	0.1	0.1	-0.1	-0.1	-0.1
B763P	0.0	0.0	0.1	0.2	0.2	0.4	+0.2	+0.1	+0.3
B772G	1.7	1.6	3.3	4.3	3.9	8.2	+2.6	+2.3	+4.9
B772R	0.5	0.4	0.9	3.9	3.2	7.1	+3.4	+2.8	+6.2
B773G	0.0	0.0	0.0	0.3	0.3	0.6	+0.3	+0.3	+0.6
B788	0.7	0.6	1.3	2.8	1.5	4.4	+2.1	+1.0	+3.1
B789	1.2	1.2	2.4	5.5	4.3	9.9	+4.3	+3.2	+7.5
BA46	0.1	0.1	0.1	0.0	0.0	0.0	-0.1	0.0	-0.1
EA223	1.8	1.8	3.6	2.3	2.3	4.7	+0.5	+0.5	+1.1
EA319C	18.6	19.9	38.5	76.3	71.4	147.6	+57.7	+51.5	+109.2
EA319V	0.2	0.2	0.4	1.3	1.3	2.6	+1.1	+1.1	+2.1
EA320C	26.6	25.9	52.5	91.4	80.4	171.8	+64.8	+54.5	+119.4
EA320NEO	13.8	12.9	26.8	20.7	17.6	38.3	+6.9	+4.7	+11.6
EA320V	1.9	1.7	3.6	45.8	36.8	82.6	+43.9	+35.1	+79.0
EA321C	0.1	0.1	0.2	1.4	1.2	2.6	+1.3	+1.1	+2.4
EA321NEO	5.2	5.1	10.3	30.4	24.5	54.9	+25.2	+19.4	+44.6
EA321V	0.8	0.8	1.7	4.8	5.1	9.9	+3.9	+4.3	+8.3
EA33	0.0	0.1	0.1	0.7	0.6	1.3	+0.7	+0.6	+1.2
EA34	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
EA359	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
EA38GP	0.0	0.0	0.0	1.0	1.0	2.0	+1.0	+1.0	+2.0
EA38R	0.0	0.0	0.0	0.8	0.8	1.6	+0.8	+0.8	+1.6
ERJ	0.0	0.0	0.0	0.0	0.0	0.1	0.0	0.0	+0.1
ERJ190	2.7	2.7	5.4	4.4	4.4	8.7	+1.7	+1.7	+3.3
EXE3	0.4	0.4	0.9	0.5	0.5	0.9	+0.1	0.0	+0.1
L4P	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
LTT	0.3	0.3	0.6	4.9	4.9	9.8	+4.6	+4.6	+9.2
SP	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
STP	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
STT	0.1	0.0	0.1	0.0	0.0	0.0	-0.1	0.0	-0.1
Total	91.4	90.2	181.5	353.0	312.3	665.3	+261.6	+222.1	+483.7
							(+286%)	(+246%)	(+266%)

Table C3 Gatwick 2021 and 2022 average summer day movements by ANCON type

Note: All numbers are rounded to 1 decimal place. Movement changes have been calculated from unrounded numbers.

ANCON	2021	2021	2021 total	2022	2022	2022 total	Change	Change	Change
type	departures	arrivals		departures	arrivals		departures	arrivals	total
B733	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
B738	0.8	1.0	1.8	1.5	2.1	3.5	+0.7	+1.0	+1.7
B738MAX	0.6	0.8	1.4	2.0	4.4	6.4	+1.3	+3.6	+4.9
B757E	0.2	0.1	0.3	0.1	0.3	0.4	-0.1	+0.2	+0.1
B763G	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
B763P	0.0	0.0	0.0	0.0	0.1	0.1	0.0	+0.1	+0.1
B772G	0.0	0.1	0.1	0.0	0.4	0.4	0.0	+0.4	+0.3
B772R	0.0	0.1	0.1	0.0	0.7	0.7	0.0	+0.6	+0.6
B773G	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
B788	0.0	0.2	0.3	0.3	1.6	1.8	+0.2	+1.3	+1.6
B789	0.0	0.0	0.0	0.0	1.2	1.2	0.0	+1.2	+1.2
BA46	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
EA223	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
EA319C	2.0	0.7	2.7	7.8	12.7	20.5	+5.8	+12.0	+17.8
EA319V	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
EA320C	2.6	3.2	5.8	8.2	19.0	27.2	+5.6	+15.8	+21.4
EA320NEO	1.3	2.2	3.5	2.5	5.6	8.0	+1.2	+3.4	+4.6
EA320V	0.1	0.1	0.2	4.4	13.3	17.7	+4.3	+13.3	+17.5
EA321C	0.0	0.0	0.0	0.2	0.4	0.6	+0.2	+0.4	+0.6
EA321NEO	1.4	1.5	3.0	5.0	10.8	15.7	+3.5	+9.2	+12.8
EA321V	0.0	0.0	0.0	0.8	0.4	1.2	+0.8	+0.4	+1.2
EA33	0.0	0.0	0.0	0.0	0.1	0.1	0.0	+0.1	+0.1
EA34	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
EA38R	0.0	0.0	0.0	0.1	0.0	0.1	+0.1	0.0	+0.1
ERJ190	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
EXE3	0.1	0.1	0.1	0.0	0.0	0.1	-0.1	0.0	-0.1
LTT	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
STP	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
STT	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total	9.3	10.1	19.4	32.7	73.2	106.0	+23.5	+63.1	+86.6
							(+254%)	(+622%)	(+446%)

Table C4 Gatwick 2021 and 2022 average summer night movements by ANCON type

Note: All numbers are rounded to 1 decimal place. Movement changes have been calculated from unrounded numbers.

APPENDIX D

ANCON type descriptions

Table D1 ANCON type descriptions

ANCON type	Description
B717	Boeing 717
B727	Boeing 727 (Chapter 2&3)
B732	Boeing 737-200 (Chapter 2&3)
B733	Boeing 737-300/400/500
B736	Boeing 737-600/700
B738MAX	Boeing 737 MAX 8
B739MAX	Boeing 737 MAX 9
B738	Boeing 737-800/900
B747	Boeing 747-100 & 200/300 series (certificated to Chapter 3)
B744G	Boeing 747-400 with General Electric CF6-80F engines
B744P	Boeing 747-400 with Pratt & Whitney PW4000 engines
B744R	Boeing 747-400 with Rolls-Royce RB211 engines
B747SP	Boeing 747SP
B748	Boeing 747-8
B753	Boeing 757-300
B757C	Boeing 757-200 with Rolls-Royce RB211-535C engines
B757E	Boeing 757-200 with Rolls-Royce RB211-535E4/E4B engines
B757P	Boeing 757-200 with Pratt & Whitney PW2037/2040 engines
B762	Boeing 767-200
B763G	Boeing 767-300 with General Electric CF6-80 engines
B763P	Boeing 767-300 with Pratt & Whitney PW4000 engines
B763R	Boeing 767-300 with Rolls-Royce RB211 engines
B764	Boeing 767-400
B772G	Boeing 777-200 with General Electric GE90 engines
B772P	Boeing 777-200 with Pratt & Whitney PW4000 engines
B772R	Boeing 777-200 with Rolls-Royce Trent 800 engines
B773G	Boeing 777-200LR/300ER with General Electric GE90 engines
B773P	Boeing 777-300 with Pratt & Whitney PW4000 engines
B773R	Boeing 777-300 with Rolls-Royce Trent 800 engines
B788	Boeing 787-8
B789	Boeing 787-9
BA46	BAe 146/Avro RJ series
CRJ	Bombardier CRJ100/200 series

ANCON type	Description
CRJ700	Bombardier CRJ700 series
CRJ900	Bombardier CRJ900 series
DC10	McDonnell Douglas DC-10
EA221	Airbus A220-100
EA223	Airbus A220-300
EA30	Airbus A300
EA31	Airbus A310
EA318	Airbus A318
EA319C	Airbus A319 with CFM56 engines
EA319V	Airbus A319 with IAE V2500 engines
EA320C	Airbus A320 with CFM56 engines
EA320NEO	Airbus A320neo
EA320V	Airbus A320 with IAE V2500 engines
EA321C	Airbus A321 with CFM56 engines
EA321NEO	Airbus A321neo
EA321V	Airbus A321 with IAE V2500 engines
EA33	Airbus A330
EA34	Airbus A340-200/300
EA346	Airbus A340-500/600
EA359	Airbus A350-900
EA38GP	Airbus A380 with Engine Alliance GP7000 engines
EA38R	Airbus A380 with Rolls-Royce Trent 900 engines
ERJ	Embraer ERJ 135/145
ERJ170	Embraer E-170/175
ERJ190	Embraer E-190/195
EXE2	Chapter 2 executive jets
EXE3	Chapter 3 executive jets
FK10	Fokker 70/100
L101	Lockheed L-1011 TriStar
L4P	Large four-engine propeller
LTT	Large twin-turboprop
MD11	McDonnell Douglas MD-11
MD80	McDonnell Douglas MD-80 series
ANCON type	Description
------------	----------------------
SP	Single propeller
STP	Small twin-piston
STT	Small twin-turboprop
TU54	Tupolev Tu-154

Glossary

Glossary		
AIP	Aeronautical Information Publication	
AMSL	Above Mean Sea Level	
ANCON	The UK civil aircraft noise contour model, developed and maintained by ERCD.	
ATC	Air Traffic Control	
CAA	Civil Aviation Authority	
dB	Decibel units describing sound level or changes of sound level.	
DfT	Department for Transport (UK Government)	
ERCD	Environmental Research and Consultancy Department	
FOPP	Fuel Over Pressure Protector	
GAL	Gatwick Airport Limited	
ICAO	International Civil Aviation Organization	
L _{Aeq}	Equivalent sound level of aircraft noise in dBA, often called 'equivalent continuous sound level'.	
LAeq,16h	Equivalent A-weighted sound level of aircraft noise for the 16-hour daytime period (07:00- 23:00 local time)	
L _{Aeq,8h}	Equivalent A-weighted sound level of aircraft noise for the 8-hour night-time period (23:00-07:00 local time)	
L _{Amax}	A-weighted maximum sound level of a noise event.	
N60	Number of aircraft noise events above 60 dB L _{Amax} .	
N65	Number of aircraft noise events above 65 dB L _{Amax} .	
NPD	Noise-Power-Distance	
NPR	Noise Preferential Route	
NTK	Noise and Track Keeping monitoring system	
OS	Ordnance Survey, the national mapping agency of Great Britain	

Glossary		
SEL	Sound Exposure Level – the steady noise level, which over a period of one second contains the same sound energy as the whole aircraft noise event. It is equivalent to the L_{Aeq} of the noise event normalised to one second.	
SID	Standard Instrument Departure	